

TOSHIBA



CRAFTED FOR THOSE
WHO SEEK MORE

TOSHIBA Hi-Wall

The new Toshiba Hi-Wall Series represents a new era of premium cooling. Built for spaces that value elegance, silence, and superior engineering, this range blends sophisticated aesthetics with Japanese precision to elevate the way you experience comfort.

PRECISION REDEFINED THROUGH DESIGN

Every detail in the new Toshiba Hi-Wall Series is designed with purpose. With thoughtful engineering, a clean matte finish, and smooth, quiet cooling, it brings comfort to any space in a way that feels natural and welcoming.



THE MATTE FINISH OF MODERN LUXURY

Crafted with a soft matte texture and a refined silhouette, the indoor unit blends into contemporary spaces with ease. Its calm, modern finish adds to the environment without drawing attention, letting the space feel balanced and uncluttered.

REDEFINE



BUILT FOR TODAY. READY FOR TOMORROW.

The next-generation Hi-Wall Series is engineered to deliver consistent, dependable cooling across all conditions.

- **Fast, responsive cooling**
- **High-ambient capability for extreme temperatures**
- **Stable inverter performance**
- **Clear temperature display**

THE USB-RECHARGEABLE REMOTE

Your first connection to comfort should be as premium as the AC itself. Introducing the all-new USB-rechargeable remote:

- No more batteries
- Minimalist design with premium tactile buttons
- Long lasting power and sustainability
- Smooth, intuitive navigation

A remote that complements your lifestyle - stylish, modern, and thoughtful.



4-WAY FLEXIBLE SWING COMFORT

Comfort is now more personalised than ever. The advanced 4-way flexible swing ensures even cooling from corner to corner, letting air flow naturally throughout the room. Whether relaxing, working, or entertaining - every spot feels just right.

AIR THAT CARES FOR YOU

This AC protects your home with:

Advanced PM 2.5 filtration 

Nano-coating technology for longer machine life 

Cleaner airflow and reduced impurities 

Every breath feels lighter, fresher, and healthier.

COMFORT THAT CLEANS ITSELF

With Toshiba's Self-Cleaning Technology, your AC stays fresh inside-out. The fan continues to run after shutdown, preventing moisture buildup, mold formation, and odor. This means cleaner air, better performance, and longer lifespan - naturally.

ENGINEERING YOU CAN TRUST

Why choose Toshiba?

-  High ambient cooling up to 52°C
-  Whisper-quiet operation at just 23 dB(A)
-  Multiple power modes for every occasion
-  Eco-friendly performance with sustained durability

It's cooling made smarter,
stronger & more refined.



COOLING WITH RESPONSIBILITY

The new Hi-Wall Series uses R32 refrigerant-
a safer, greener choice.

- Lower Global Warming Potential
- Zero ozone depletion
- Better energy efficiency

Making Luxury Responsible.

TOSHIBA

Hi-Wall



TOSHIBA SERVICE HELPLINE
1800 3000 3545
1800 1021 421

For more details, please contact our sales office:

Corporate & Registered Office: Carrier Airconditioning & Refrigeration Ltd, Kherki Daula Post, Narsingpur, Gurgaon 122004,
Tel: 0124-4825500 **Sales Offices:-** **Ahmedabad:** 079-44820400/401 **Ghaziabad:** 0120-4183260 **Bangalore:** 080-43442000
Bhubaneswar: 9778030033 **Chandigarh:** 0172-5007549/50 **Chennai:** 044-66448888 **Cochin:** 0484-4029000/001, **Coimbatore:**
739744420 **Daryaganj:** 011-23244491, 9810973264 **Delhi/NCR:** 0124-4873200 **Goa:** 9987868667 **Guwahati:** 9831079624
Hyderabad: 040-4181 2222 **Indore:** 0731-2445200 **Jaipur:** 0141-4921737 / 738 **Kolkata:** 033-40592000/3000 **Lucknow:**
0522-4158701/704 **Navi Mumbai/Thane:** 9167788252 **Mumbai:** 022-61700700 **Nagpur:** 9881714903 **Patna:** 7070621177 **Pune:**
020-48571000 **Raipur:** 9752542882 **Surat:** 7433920332

CIN: U74999HR1992FLC036104/ **Website:** www.carrierindia.com, www.toshibaac.in, E-mail: info@toshibaac.in | customersupport@carrier.com



TOTALINE

CRAFTED FOR THOSE WHO SEEK MORE

TOSHIBA Hi-Wall

MADE FOR EVERY
PREMIUM SPACE

Choose the perfect fit for your space:

Model	Indoor	RAS-13P5KCV3XGQ-IN	RAS-18P5KCV3XGQ-IN	RAS-24P5KCV3XGQ-IN
	Outdoor	RAS-13P5ACV3XGQ-IN	RAS-18P5ACV3XGQ-IN	RAS-24P5ACV3XGQ-IN
Capacity	kW	3.6 (1.6-3.7)	5.2(2.1-5.4)	6.4(2.8-6.8)
Power Consumption				
ISEER		4.40	4.40	4.40
Star Rating		3	3	3
Indoor Packing Dimension (W x D X H)	mm	1030 x 395 x 302	1030 x 395 x 302	1171 x 430 x 322
Indoor Unit Dimension (W x D X H)	mm	960 x 314 x 226	960 x 314 x 226	1100 x 356 x 248
Airflow	CMH (Dry)	1020	1050	1450
	CFM (Dry)	600	618	853
Indoor Sound Pressure (Hi- Power/ High/ Medium/ Low/ Silent)	dB (A)	46/44/39/34/32	48/44/39/34/32	49/46/43/39/34
Outdoor Packing Dimension (W x D X H))	(mm)	910 x 345 x 590	910 x 345 x 590	910 x 395 x 590
Outdoor Unit Dimension (W x D X H)	(mm)	835 x 297 x 560	835 x 297 x 560	835 x 352 x 560
Outdoor Sound Pressure	(dB (A)	54	53	54
Ambient operation	Min (°C)	15	15	15
	Max (°C)	52	52	52
Piping connections	Liquid side (mm)	6.00	6.00	6.00
	Gas side (mm)	9.00	12.00	12.00
Pipe length	Total length (m)	15	15	15
	inclusive of vertical lift (m)	5	5	5
Refrigerant		R32		

With Kit Models *RAS-xxP5xCVxXGQ-IT

Suited for bedrooms, living rooms, offices, and contemporary interiors.
Followed by the Specification Table



- Suited for bedrooms, living rooms, offices, and contemporary interiors
- Followed by the Specification Table

Available in 3-Star and 5-Star variants Tonnage options: 1 Ton, 1.5 Ton, 2 Ton

RAS-13P5KCV5XGQ-IN	RAS-18P5KCV5XGQ-IN	RAS-24P5KCV5XGQ-IN
RAS-13P5ACV5XGQ-IN	RAS-18P5ACV5XGQ-IN	RAS-24P5ACV5XGQ-IN
3.4(1.7-4.0)	5.2(2.2-5.5)	6.2(3.1-6.8)
5.60	5.65	5.65
5	5	5
1030 x 395 x 302	1171 x 430 x 322	1171 x 430 x 322
960 x 314 x 226	1100 x 356 x 248	1100 x 356 x 248
1050	1450	1320
618	853	777
48/44/39/34/32	49/46/43/39/34	49/46/43/39/34
910 x 395 x 590	908 x 395 x 610	1040 x 470 x 765
835 x 352 x 560	835 x 352 x 562	956 x 390 x 702
56	55	55
15	15	15
52	52	52
6.00	6.00	9.00
12.00	12.00	15.88
15	15	15
5	5	5
R32		

Notes:
Rated conditions: Indoor air temperature 27°C DB / 19°C WB, Outdoor air temperature 35°C DB. Star rating as per the standards & labeling program of the Bureau of Energy Efficiency. Airflow is measured at high fan speed.